

## TECHNICAL SPECIFICATION

# DRYING HOPPERS HP Series

Bulletin : BAA:HP-904.7  
Effective : FEB. 19, 2020  
Supersedes : BAA:HP-904.6  
Dated : JAN. 10, 2017

- Insulated double wall construction in CRS
- Sight glass for checking material level
- Slide gate to control material flow
- Removable air distribution cone for uniform air distribution
- Clean out door\*
- Loader mounting arrangement for automatic loading
- Machine/floor mounted
- Emergency drain out for quick change of batch
- Quick openable latches for top cover removal



\* Not available in model HP-30 & 65

### Specifications for HP-Series Drying Hoppers

MODEL	VOLUME IN LTR	APPROXIMATE HEIGHT (IN MM)			DIA METER (IN MM)		LINE SIZE (IN MM)	LEG BRACKET MOUNTING DETAIL				CLEAN OUT DOOR	INSULATED HOPPER WEIGHT IN KG
		H	H1	H2	D1	D2		E	F	G	QTY.		
HP-4	32	334	326	380	400	452	50	120	558	415	3	NO	23
HP-8	65	534	316	380	400	452	50	120	558	415	3	NO	42
HP-12	100	879	341	610	400	452	50	120	558	415	3	YES	60
HP-20	165	856	244	610	510	562	50-75	120	670	517	3	YES	88
HP-30	250	1256	244	560	510	562	75-100	120	670	517	3	YES	116
HP-40	360	1246	294	560	610	662	100	120	772	619	3	YES	132
HP-60	485	1554	282	570	610	662	100	120	772	619	3	YES	141
HP-80 DR	565	1694	306	520	660	712	100	90	822	669	4	YES	160
HP-80	700	1553	357	470	760	812	100	90	924	770	4	YES	188
HP-100	950	1937	303	445	810	862	100-150	90	975	820	4	YES	244
HP-120	1000	1565	425	395	915	967	100-150	90	1076	920	4	YES	260
HP-160	1330	2063	437	395	915	967	100-150	90	1076	920	4	YES	300
HP-200	1600	2490	410	410	915	967	100-150	90	1076	920	4	YES	340
HP-300	2500	2162	988	-	1220	1272	100-200	45	1370	N/A	8	YES	457
HP-400	4070	1964	1121	-	1524	1576	200-250	45	1669	N/A	8	YES	550

ALL DATA SUBJECT TO CHANGE WITHOUT NOTICE



